



Sept 2010

Packaging Details – Non Composite Products¹

Nominal Thickness	Bundle		Truckload		Weight ²	
	Pieces	SqFt ³	Pieces	SqFt ³	Lbs per Sqft	Lbs per Peice ³
0.5 ⁴	96	3,072	2,304	73,728	0.08	2.7
0.625 ⁴	76	2,432	1,824	58,368	0.10	3.3
0.75 ^{4,5}	64	2,048	1,536	49,152	0.13	4.0
0.75 ^{4,6}	60	1,920	1,440	46,080	0.13	4.0
1	48	1,536	1,152	36,864	0.17	5.3
1.1	43	1,376	1,032	33,024	0.09	2.9
1.2	40	1,280	960	30,720	0.20	6.4
1.25	38	1,216	912	29,184	0.21	6.7
1.3	36	1,152	864	27,648	0.22	6.9
1.4	34	1,088	816	26,112	0.23	7.5
1.5	32	1,024	768	24,576	0.25	8.0
1.6	30	960	720	23,040	0.27	8.5
1.7	28	896	672	21,504	0.28	9.1
1.75	27	864	648	20,736	0.29	9.3
1.8	26	832	624	19,968	0.30	9.6
1.9	25	800	600	19,200	0.32	10.1
2	24	768	576	18,432	0.33	10.7
2.1	22	704	528	16,896	0.35	11.2
2.2	21	672	504	16,128	0.37	11.7
2.25	21	672	504	16,128	0.38	12.0
2.3	20	640	480	15,360	0.38	12.3
2.4	20	640	480	15,360	0.40	12.8
2.5	19	608	456	14,592	0.42	13.3
2.6	18	576	432	13,824	0.43	13.9
2.7	17	544	408	13,056	0.45	14.4
2.75	17	544	408	13,056	0.46	14.7
2.8	17	544	408	13,056	0.47	14.9
2.9	16	512	384	12,288	0.48	15.5
3	16	512	384	12,288	0.50	16.0
3.1	15	480	360	11,520	0.52	16.5
3.2	15	480	360	11,520	0.53	17.1
3.25	14	448	336	10,752	0.54	17.3
3.3	14	448	336	10,752	0.55	17.6
3.4	14	448	336	10,752	0.57	18.1
3.5	13	416	312	9,984	0.58	18.7
3.6	13	416	312	9,984	0.60	19.2
3.7	12	384	288	9,216	0.62	19.7
3.75	12	384	288	9,216	0.63	20.0
3.8	12	384	288	9,216	0.63	20.3
3.9	12	384	288	9,216	0.65	20.8
4	12	384	288	9,216	0.67	21.3
4.5	10	320	240	7,680	0.75	24.0

¹ Durasheath-3, Eco-Max, Multi-Max FA-3, R-Matte Plus-3, Re-Cover Board-3, Thermasheath-3, Thermarroof Plus-3, TSA-FA-3, TSP-3, TSX-8500, TSX-8510 and Ultra-Max where applicable.

² All bundles are approximately 250 lbs.

³ Data is based on 48" x 96" pieces.

⁴ 1/2"-5/8"-3/4" are sold as full bundles, but typically packaged in half packs.

⁵ Applicable for Tapered Thermarroof-3 and Re-Cover Board-3.

⁶ Applicable for R-Matte Plus-3 and Eco-Max.



Sept 2010

Packaging Details – Nailable Base-3

Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
1.5	32	1,024	768	24,576	1,771	1.73	55.3
1.6	30	960	720	23,040	1,676	1.75	55.9
1.7	28	896	672	21,504	1,579	1.76	56.4
1.75	27	864	648	20,736	1,530	1.77	56.7
1.8	26	832	624	19,968	1,480	1.78	56.9
1.9	25	800	600	19,200	1,437	1.80	57.5
2	24	768	576	18,432	1,392	1.81	58.0
2.1	22	704	528	16,896	1,288	1.83	58.5
2.2	21	672	504	16,128	1,240	1.85	59.1
2.25	21	672	504	16,128	1,246	1.85	59.3
2.3	20	640	480	15,360	1,192	1.86	59.6
2.4	20	640	480	15,360	1,203	1.88	60.1
2.5	19	608	456	14,592	1,153	1.90	60.7
2.6	18	576	432	13,824	1,102	1.91	61.2
2.7	17	544	408	13,056	1,049	1.93	61.7
2.75	17	544	408	13,056	1,054	1.94	62.0
2.8	17	544	408	13,056	1,059	1.95	62.3
2.9	16	512	384	12,288	1,005	1.96	62.8
3	16	512	384	12,288	1,013	1.98	63.3
3.1	15	480	360	11,520	958	2.00	63.9
3.2	15	480	360	11,520	966	2.01	64.4
3.25	14	448	336	10,752	905	2.02	64.7
3.3	14	448	336	10,752	909	2.03	64.9
3.4	14	448	336	10,752	917	2.05	65.5
3.5	13	416	312	9,984	858	2.06	66.0
3.6	13	416	312	9,984	865	2.08	66.5
3.7	12	384	288	9,216	805	2.10	67.1
3.75	12	384	288	9,216	808	2.10	67.3
3.8	12	384	288	9,216	811	2.11	67.6
3.9	12	384	288	9,216	818	2.13	68.1
4	12	384	288	9,216	824	2.15	68.7
4.1	11	352	264	8,448	761	2.16	69.2
4.2	11	352	264	8,448	767	2.18	69.7
4.25	11	352	264	8,448	770	2.19	70.0
4.3	11	352	264	8,448	773	2.20	70.3
4.4	10	320	240	7,680	708	2.21	70.8
4.5	10	320	240	7,680	713	2.23	71.3

¹ Includes 7/16" OSB.

² Data is based on 48" x 96" pieces.



Sept 2010

Packaging Details – Vented Nailable Base-3							
Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
2.5	19	608	456	14,592	1,435	2.36	75.5
2.6	18	576	432	13,824	1,370	2.38	76.1
2.7	17	544	408	13,056	1,302	2.39	76.6
2.8	17	544	408	13,056	1,311	2.41	77.1
2.9	16	512	384	12,288	1,243	2.43	77.7
3	16	512	384	12,288	1,251	2.44	78.2
3.1	15	480	360	11,520	1,181	2.46	78.7
3.2	15	480	360	11,520	1,190	2.48	79.3
3.3	14	448	336	10,752	1,117	2.49	79.8
3.4	14	448	336	10,752	1,124	2.51	80.3
3.5	13	416	312	9,984	1,052	2.53	80.9
3.6	13	416	312	9,984	1,058	2.54	81.4
3.7	12	384	288	9,216	983	2.56	81.9
3.8	12	384	288	9,216	990	2.58	82.5
3.9	12	384	288	9,216	996	2.59	83.0
4	12	384	288	9,216	1,002	2.61	83.5
4.1	11	352	264	8,448	925	2.63	84.1
4.2	11	352	264	8,448	931	2.64	84.6
4.3	11	352	264	8,448	936	2.66	85.1
4.4	10	320	240	7,680	857	2.68	85.7
4.5	10	320	240	7,680	862	2.69	86.2
4.6	10	320	240	7,680	867	2.71	86.7
4.7	10	320	240	7,680	873	2.73	87.3
4.8	10	320	240	7,680	878	2.74	87.8
4.9	9	288	216	6,912	795	2.76	88.3
5	9	288	216	6,912	800	2.78	88.9
5.1	9	288	216	6,912	805	2.79	89.4
5.2	9	288	216	6,912	809	2.81	89.9
5.3	9	288	216	6,912	815	2.83	90.5
5.4	8	256	192	6,144	728	2.84	91.0
5.5	8	256	192	6,144	732	2.86	91.5

¹ Includes 7/16" OSB and 1" air space (furring strips).

² Data is based on 48" x 96" pieces.



Sept 2010

Packaging Details – Mult-Vent Nailable Base-3

Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
2.5	19	608	456	14,592	1,198	1.97	63.0
2.6	18	576	432	13,824	1,145	1.99	63.6
2.7	17	544	408	13,056	1,090	2.00	64.1
2.8	17	544	408	13,056	1,099	2.02	64.6
2.9	16	512	384	12,288	1,043	2.04	65.2
3	16	512	384	12,288	1,051	2.05	65.7
3.1	15	480	360	11,520	993	2.07	66.2
3.2	15	480	360	11,520	1,002	2.09	66.8
3.3	14	448	336	10,752	942	2.10	67.3
3.4	14	448	336	10,752	949	2.12	67.8
3.5	13	416	312	9,984	889	2.14	68.4
3.6	13	416	312	9,984	896	2.15	68.9
3.7	12	384	288	9,216	833	2.17	69.4
3.8	12	384	288	9,216	840	2.19	70.0
3.9	12	384	288	9,216	846	2.20	70.5
4	12	384	288	9,216	852	2.22	71.0
4.1	11	352	264	8,448	788	2.24	71.6
4.2	11	352	264	8,448	793	2.25	72.1
4.3	11	352	264	8,448	799	2.27	72.6
4.4	10	320	240	7,680	732	2.29	73.2
4.5	10	320	240	7,680	737	2.30	73.7
4.6	10	320	240	7,680	742	2.32	74.2
4.7	10	320	240	7,680	748	2.34	74.8
4.8	10	320	240	7,680	753	2.35	75.3
4.9	9	288	216	6,912	682	2.37	75.8
5	9	288	216	6,912	682	2.39	75.8
5.1	9	288	216	6,912	692	2.40	76.9
5.2	9	288	216	6,912	697	2.42	77.4
5.3	9	288	216	6,912	702	2.44	78.0
5.4	8	256	192	6,144	628	2.45	78.5
5.5	8	256	192	6,144	632	2.47	79.0

¹ Includes 7/16" OSB and 1" air space (blocks).

² Data is based on 48" x 96" pieces.



Sept 2010

Packaging Details – Thermaroof Composite-3

Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
1.5	32	1,024	768	24,576	551	0.54	17.2
1.6	30	960	720	23,040	532	0.55	17.7
1.7	28	896	672	21,504	512	0.57	18.3
1.75	27	864	648	20,736	500	0.58	18.5
1.8	26	832	624	19,968	489	0.59	18.8
1.9	25	800	600	19,200	483	0.60	19.3
2	24	768	576	18,432	477	0.62	19.9
2.1	22	704	528	16,896	449	0.64	20.4
2.2	21	672	504	16,128	440	0.65	20.9
2.25	21	672	504	16,128	445	0.66	21.2
2.3	20	640	480	15,360	429	0.67	21.5
2.4	20	640	480	15,360	440	0.69	22.0
2.5	19	608	456	14,592	428	0.70	22.5
2.6	18	576	432	13,824	415	0.72	23.1
2.7	17	544	408	13,056	401	0.74	23.6
2.75	17	544	408	13,056	406	0.75	23.9
2.8	17	544	408	13,056	410	0.75	24.1
2.9	16	512	384	12,288	395	0.77	24.7
3	16	512	384	12,288	403	0.79	25.2
3.1	15	480	360	11,520	386	0.80	25.7
3.2	15	480	360	11,520	394	0.82	26.3
3.25	14	448	336	10,752	372	0.83	26.5
3.3	14	448	336	10,752	375	0.84	26.8
3.4	14	448	336	10,752	383	0.85	27.3
3.5	13	416	312	9,984	362	0.87	27.9
3.6	13	416	312	9,984	369	0.89	28.4
3.7	12	384	288	9,216	347	0.90	28.9
3.75	12	384	288	9,216	350	0.91	29.2
3.8	12	384	288	9,216	354	0.92	29.5
3.9	12	384	288	9,216	360	0.94	30.0
4	12	384	288	9,216	366	0.95	30.5
4.1	11	352	264	8,448	342	0.97	31.1
4.2	11	352	264	8,448	348	0.99	31.6
4.25	11	352	264	8,448	351	1.00	31.9
4.3	11	352	264	8,448	354	1.00	32.1
4.4	10	320	240	7,680	327	1.02	32.7
4.5	10	320	240	7,680	332	1.04	33.2

¹ Includes 1/2" perlite.

² Data is based on 48" x 96" pieces.